



| Type        | Output | Speed | Amps | EFF. | P. F.      | LRT/RLT | LRA/RLA | BDT/RLT | Voltage | Bearing |      |
|-------------|--------|-------|------|------|------------|---------|---------|---------|---------|---------|------|
|             | kW     | r/min | A    | %    | cos $\phi$ |         |         |         | V       | DE      | NDE  |
| PID-160M1-2 | 11     | 2940  | 18.9 | 91.2 | 0.89       | 2       | 8.5     | 2.3     | 415     | 6309    | 6309 |
| PID-160M2-2 | 15     | 2950  | 25.5 | 91.9 | 0.89       | 2       | 8.5     | 2.3     | 415     | 6309    | 6309 |
| PID-160M-4  | 11     | 1465  | 19.7 | 91.4 | 0.85       | 2.2     | 7.7     | 2.3     | 415     | 6309    | 6309 |
| PID-160M-6  | 7.5    | 970   | 14.8 | 89.1 | 0.79       | 2       | 7       | 2.1     | 415     | 6309    | 6309 |
| PID-160M1-8 | 4      | 725   | 9.0  | 84.8 | 0.73       | 1.9     | 6.9     | 2       | 415     | 6309    | 6309 |
| PID-160M2-8 | 5.5    | 725   | 12.0 | 86.2 | 0.74       | 1.9     | 6.9     | 2       | 415     | 6309    | 6309 |

|                  |  |  |                    |
|------------------|--|--|--------------------|
| DRAWN            |  |  | PID-160M B5        |
| CHECKED          |  |  |                    |
| Perdurus Pty Ltd |  |  | OUTLINE DIMENSIONS |