



| Type | Output | Speed | Amps | EFF. | P. F. | LRT/RLT | LRA/RLA | BDT/RLT | Voltage | Bearing | |
|------------|--------|-------|------|------|------------|---------|---------|---------|---------|---------|------|
| | kW | r/min | A | % | cos ϕ | | | | | DE | NDE |
| PID-280S-4 | 75 | 1485 | 125 | 95.0 | 0.88 | 2 | 6.9 | 2.3 | 415 | 6317 | 6317 |
| PID-280S-6 | 45 | 985 | 78.6 | 93.7 | 0.85 | 2 | 7.3 | 2 | 415 | 6317 | 6317 |
| PID-280S-8 | 37 | 740 | 71.0 | 91.8 | 0.79 | 1.9 | 6.7 | 2 | 415 | 6317 | 6317 |
| PID-280M-4 | 90 | 1485 | 149 | 95.2 | 0.88 | 2 | 6.9 | 2.3 | 415 | 6317 | 6317 |
| PID-280M-6 | 55 | 985 | 94.6 | 94.1 | 0.86 | 2 | 7.3 | 2 | 415 | 6317 | 6317 |
| PID-280M-8 | 45 | 740 | 85.9 | 92.2 | 0.79 | 1.9 | 6.7 | 2 | 415 | 6317 | 6317 |

| | | | |
|------------------|--|--------------------|-------------------|
| DRAWN | | | PID-280SM-4~8 B35 |
| CHECKED | | | |
| Perdurus Pty Ltd | | OUTLINE DIMENSIONS | |